

GDB Circular (MN), Inc.

19850 S Diamond Lake Rd Suite 100 Rogers, MN 55374

+732-246-3001

www.gdbcircular.com



Technical Data Sheet (TDS) LDPE/LLDPE Blended PCR - Clear - Tier B

Product Name

Technical Data:

Shape: Die cut (spherical) resin

Color: Clear/Natural

Application: General Extrusion, Blow

Molding, Film extrusion

Specification:

GDB Grade: PCR100-MNLD-CL-TB Higher gel count than Tier A PCR

Material Name: rLDPE Compounding: 100% PCR Balanced LDPE & LLDPE

Features

- ✓ ISO 14001:2015 Compliant Produced from post-consumer goods
- ✓ California Prop 65 Compliant Lead and Cadmium

Properties			
Test Type	Units	Results	Test Method
Melt Flow Rate	g/10 mins	0.40 – 1.40	ISO 1133
Density	g/cc	0.910 - 0.935	ISO 1183
Ash	wt. %	< 2.0	ISO 3451
L*	value	> 40	ISO 11664

Version: January 2025

All equipment is calibrated annually to a NIST traceable standard. All equipment was verified to be working properly prior to all testing conducted.

Prior to utilizing this product, users are strongly advised to independently assess its safety and suitability for the specific intended purpose. The user bears full responsibility for ensuring the product's appropriateness and the relevance of the information to their application. GDB International Inc. completely disclaims all warranties, whether oral or written, express or implied, including but not limited to merchantability or fitness for a specific purpose. These disclaimers apply regardless of any alleged warranties arising from trade usage or prior dealings. Any risks and liabilities associated with the use of the product, or the information provided herein are assumed by the user, whether arising from contract, tort, or any other legal basis.